



## GWE Well Hood

**Above-ground well  
closure with pre-  
mounted well head  
and pipeworks  
pipe system**

### Advantages

- ✓ CE label with declaration of conformity
- ✓ Rapid installation with pre-mounted well head and pipeworks pipe system
- ✓ Strong protection against unauthorized opening (safety lock and additional padlock)
- ✓ Integrated control box in protection class IP65 (dustproof and impermeable)
- ✓ UV-resistant housing surface made of polyester-glass laminate (gel coat)
- ✓ Double-walled thermally insulated housing with sandwich design
- ✓ Thermostat-controlled radiator heating for full frost protection
- ✓ LED illumination



## GWE Well Hood – the pre-mounted above-ground well closure structure

The GWE Well Hood offers safe and reliable protection for wells and water collection systems in factories, sporting facilities and parks, as well as facilities for agricultural irrigation. With the GWE Well Hood, the well and the installed water fittings are protected against unauthorized access and against the

penetration of surface water. The GWE Well Hood is easy to open and close, requiring just one person for regular inspections and smaller repairs. Thanks to the double-walled housing and integrated heating, operations are guaranteed even in permafrost conditions.

### Basic equipment

- Well head with riser pipe connection DN 50 to DN 150
- Pre-mounted pipeworks pipe system comprising:
  - Check valve
  - Pipe bend (Q piece)
  - Water meter
  - Throttle valve
  - Pressure gauge with valve
  - Thermostat-controlled 250 W heating

### Optional accessories:

- Inductive flow rate meter
- Sampling valve
- Fire hydrant connection 2" (C-clutch)
- Customer logo
- Special colors



**Additional equipment and further accessories possible after prior consultation.**

